

# IALA Guideline No. 1081

On

Provision of

Virtual Aids to Navigation

Edition 1.1

May 2013

Edition 1 March 2010



10 rue des Gaudines

78100 Saint Germain en Laye, France

Telephone: +33 1 34 51 70 01 Fax: +33 1 34 51 82 05

e-mail: [contact@iala-aism.org](mailto:contact@iala-aism.org) Internet: [www.iala-aism.org](http://www.iala-aism.org)

## DOCUMENT REVISIONS

Revisions to the IALA Document are to be noted in the table prior to the issue of a revised document.

Date	Page / Section Revised	Requirement for Revision
May 2013	Minor amendments throughout the document	To reflect developments at IMO NAV discussion on AIS AtoN.

## TABLE OF CONTENTS

Document Revisions	2
Table of Contents	3
Index of Tables	4
Index of Figures	4
Virtual Aids to Navigation	5
1 Introduction	5
2 Scope	5
3 Purpose	5
4 Defining a Virtual Aid to Navigation	5
4.1 Definition	5
4.2 Amplification	5
5 Application of Virtual AtoN	6
5.1 User needs	6
5.1.1 Advice to AtoN Authorities	6
5.1.2 Advice to Mariners	7
5.2 Benefits	7
6 Technical Deployment of Virtual AtoN	7
7 Regulatory Issues	8
7.1 Authority to deploy	8
7.2 Capability	8
7.3 Liability	8
8 Delivery methods	8
8.1 Technical aspects	8
8.2 Display	9
8.2.1 General	9
8.2.2 Limitations	9
8.2.3 Symbols	9
8.2.4 Point and Area Representation	10
8.2.5 Expiry and cancellation of virtual AtoN objects	10
9 Notification	10
10 Risks and limitations	11
10.1 Risk Mitigation	11
10.2 Limitations	12
10.2.1 GNSS vulnerability	12
10.2.2 Spoofing and Jamming of Virtual AtoN	13
10.2.3 AIS VDL capacity and FATDMA planning	13
10.2.4 Display Limitations	13

11	Level of Service	13
11.1	Availability	13
11.2	Integrity alerting	14
11.3	Continuity	14
12	Development considerations	14
13	References	15
14	Acronyms / Initialisms	16
ANNEX A	Application of Virtual Aids to Navigation	18

## **INDEX OF TABLES**

Table 1	Potential risk mitigation measures	11
---------	------------------------------------	----

## **INDEX OF FIGURES**

Figure 1	The symbol for an AIS AtoN	9
----------	----------------------------	---

## VIRTUAL AIDS TO NAVIGATION

### 1 INTRODUCTION

IALA recognises that there are various tools available for use by Aids to Navigation (AtoN) authorities to improve and enhance services to mariners. Among these are visual, radio and now, virtual AtoN.

This document offers national members and other authorities guidance on the provision of virtual AtoN.

### 2 SCOPE

This document provides guidance on the use of virtual AtoN risks and benefits, criteria for application, notification process, display, application and delivery methods, applicable standards and guidelines, availability and integrity, legal and liability issues.

This document is a general guide only and is not intended to specify in detail when or how to deploy virtual AtoN. Appropriate sources (see references) should be consulted for additional relevant information.

The concept of virtual AtoN has its roots in AIS but in the future other means of transmission and presentation may evolve. References to AIS in this document should not be construed as limiting virtual AtoN to that system.

### 3 PURPOSE

The purpose of this Guideline is to inform AtoN authorities, mariners and equipment manufacturers of the value and uses of Virtual AtoN. It will assist administrations and authorities in determining the appropriate uses for and the means to establish and operate virtual AtoN. This Guideline will assist shipmasters, pilots and other mariners in realizing the benefits, limitations and the inherent risks involved when using virtual AtoN as a means to verify their position, determine a safe course to steer or to avoid dangers. This Guideline will assist marine electronics equipment manufacturers in designing and marketing the next generation of shipboard navigation display systems. Finally, maritime training institutes may also wish to avail themselves of the information contained herein in order to develop syllabi that will prepare seafarers to take advantage of this emerging technology.

### 4 DEFINING A VIRTUAL AID TO NAVIGATION

#### 4.1 Definition

A virtual AtoN does not physically exist but is a digital information object<sup>1</sup> promulgated by an authorised service provider that may be presented on navigational systems.

#### 4.2 Amplification

Virtual AtoN should only be used after approval by a national competent authority.

Virtual AtoN can be used to inform the mariner about dangers to navigation as well as safe waterways, areas in which extra caution may be necessary and areas to be avoided.

They may be used to represent a line, area, position or other form that may be displayed graphically.

The information, including geographic position, carried by virtual AtoN may be fixed or may be changed over time (dynamic), depending on the intended purpose.

---

<sup>1</sup> An item or group of items, regardless of type or format that a computer can address or manipulate as a single object that will inform the user as to the characteristic of a virtual AtoN.

Virtual AtoN are used primarily where there is a time critical consideration. They may also be used in places where permanent physical AtoN cannot be sited or maintained. However, they are not intended to replace physical AtoN.

There are two applications of Virtual AtoN, temporary and permanent and they should be reflected in Maritime Safety Information (MSI) and be shown on the relevant nautical paper chart, Electronic Navigational Chart (ENC) and other relevant nautical publications in due course.

## **5 APPLICATION OF VIRTUAL AtoN**

Virtual AtoN can provide early notification to the mariner of urgent, temporary or dynamic information. Virtual AtoN should not, in general, be considered as a replacement for other forms of MSI but can provide a valuable supplementary delivery mechanism, enabling an automated graphical display of MSI otherwise only available in textual form. In certain circumstances, refer to the chapter 5 of the IALA Recommendation O-143 on the Provision of Virtual Aids to Navigation, Virtual AtoN can be also used as permanent marking. Specific applications are described at the Annex 1 of this Guideline.

### **5.1 User needs**

Users will include mariners and shore side authorities.

User needs may include presentation of information on:

- new hazards (fixed or dynamic);
- temporary channels or routes;
- temporary areas to be avoided (e.g. survey / dredging/ fishing / yacht racing);
- changed hydrography;
- temporary replacement of off station physical AtoN;
- dynamic areas (e.g. reduced visibility, presence of protected species);
- Polar navigation;
- ice conditions and navigation;
- incident response (e.g. environmental, SAR);
- port specific applications (e.g. passage planning, amended pilot boarding location, etc.);
- measures for the protection of the marine environment;
- security.

#### **5.1.1 Advice to AtoN Authorities**

In using virtual AtoN the following are among the issues that need to be considered:

- carrying out a proper risk assessment to ascertain the need for virtual AtoN;
- be aware of over proliferation and use virtual AtoN where appropriate;
- take into account the vulnerability of Global Navigation Satellite System (GNSS) systems;
- take into account the limitation of display systems on receiving ships;
- promulgate the information widely to different users;
- mixture of other AtoN located in such area;
- take into account the limitation of virtual AtoN technology such as code;

- take into account the limitation of data link load, numbers allocated, e.g. Maritime Mobile Service Identity (MMSI) numbers for AIS, etc.

#### 5.1.2 Advice to Mariners

In using virtual AtoN the following are among the issues that need to be considered:

- avoidance of reliance on single sources of information;
- refer to MSI;
- be aware of the possibility of different symbols on different systems;
- be aware of limitations of virtual AtoN provision and presentation;
- difference between virtual and physical AIS AtoN (real and synthetic) ;
- the need to maintain situational awareness by comparing electronic and non-electronic means;
- the need to avoid target fixation;
- be aware of cluttering affect caused by too many AIS information;
- many systems, including AIS, are GNSS dependent for position and timing and subject to the same vulnerabilities.

## 5.2 Benefits

Some of the potential benefits of virtual AtoN in enhancing safety, environment and security are:

- timely notification;
- ease and accuracy of presentation, where displayed graphically;
- ease and speed of deployment;
- direct delivery to navigational systems; limited to relevant area;
- information readily apparent to the user;
- avoidance of misinterpretation through use of standardised symbology and IMO phraseology;
- easily changed / amended;
- low cost to install and maintain;
- marking where physical AtoN is not practical.

## 6 TECHNICAL DEPLOYMENT OF VIRTUAL AtoN

Information from the virtual AtoN services should be broadcast to shipboard receivers by more than one means. The navigation information provided for virtual AIS AtoN must be repeated in MSI broadcasts to assure that all mariners receive safety information. Virtual AIS AtoN messages should include a reference to identify the associated MSI message. Reference could be provided in the Message 21 field 'Name of AtoN Extension'. (see Reference [20].) The 'Name of AtoN Extension' needs to be considered on a wider scale when developing new message definitions for virtual AtoN delivery. (See section 8.1)

The navigation information needs to be displayed on Electronic Chart Display & Information System (ECDIS), Electronic Chart System (ECS) and on radar equipment. These displays should indicate the information graphically as well as provide text display of detailed information when available in addition to the graphic.

There may be a limit to the number of virtual AtoN and / or their reporting interval (update rate) that can be in the same area due to limitations in the capacity of the communication link. There may

also be a limitation on the shipboard processing capability.

To mark areas, AIS binary application specific messages may be used, rather than multiple virtual AIS AtoN (Message 21). There is a limit to the number of virtual AIS AtoN that can be in the same area due to available timeslots in the AIS system. Multiple virtual AIS AtoN (Message 21) could increase clutter on the display. The authority needs to be aware that the number of MMSI available for use by AIS AtoN is a finite resource (1000 per designated area code) and for this reason another means of unique identification, linking virtual AtoN to relevant MSI or chart objects may need to be considered in the future.

MMSI numbers are normally assigned to a transmitting device. For virtual AIS AtoN using Message 21, the MMSI number represents the unique identity of the AtoN itself, rather than the transmitting source. The repeat indicator is used to identify whether the signal is transmitted from another station.

## **7 REGULATORY ISSUES**

### **7.1 Authority to deploy**

SOLAS Chapter V Regulation 13 (Establishment and operation of aids to navigation) states, in part, that 'each Contracting Government undertakes to provide, as it deems practical and necessary, either individually or in co-operation with other Contracting Governments, such aids to navigation as the volume of traffic justifies and the degree of risk requires.'

Under SOLAS, Contracting Governments are obliged to provide aids to navigation, subject to IALA Recommendations and Guidelines and based on the navigational requirements for waters under their jurisdiction. However, SOLAS allows administrations significant discretion in determining what would be an appropriate mix of visual, radio and now virtual aids to navigation to meet the needs of mariners.

Section 10 of this document is intended to assist administrations to assess the risk associated with virtual AtoN for this purpose.

### **7.2 Capability**

A Contracting Government has an obligation under SOLAS to provide AtoN. This obligation is exercised by the appropriate entity (usually a national administration). This entity should also be responsible for determining who may be permitted to deploy virtual AtoN. Typically, a VTS, Harbour Master, Rescue Co-ordination Centre (RCC) or some other entity may have the capability to deploy virtual AtoN.

The lines of authority between the Contracting Government and the entity deploying virtual AtoN should be clearly delineated. Roles and responsibilities at all levels should be clearly defined.

### **7.3 Liability**

Virtual AtoN are simply another type of Aid to Navigation. Having elected to deploy a virtual AtoN, an administration should be able to establish that the virtual AtoN is being provided as promulgated and is operating correctly.

It is likely that an administration's exposure to liability from deploying a virtual AtoN will be similar to that for any other Aid to Navigation. Therefore, noting the unique nature of virtual AtoN, robust processes and procedures for approval, promulgating information about them, together with integrity monitoring and record keeping, should be established.

## **8 DELIVERY METHODS**

### **8.1 Technical aspects**

This guideline addresses near term and long term alternatives for delivery of a virtual AtoN service.

In the near term, shore based AIS networks provide competent authorities with means to operate an information service for shore-based VTS, traffic management schemes, ship reporting systems

and other shore-based safety-related services, including virtual AtoN services. This service consists of information delivery between ships and shore and vice versa.

Technical details of the AIS technology and of the layout and local configuration of shore-based AIS are described in IALA Recommendation A-124.

In the longer term, authorities may expect that other media for information services will become available. This would enable virtual AtoN services to be transmitted via means other than AIS, for example: sitcom / internet; WiMAX; LORAN; DGPS - IALA maritime beacon system; GPRS cell phone data transmission protocol.

In the near term, not all vessels can be expected to be able to effectively display virtual AtoN information. As of July 2008 SOLAS Radars are required to interface to AIS and display AIS information, as in MSC Resolution 192(79). Although ECDIS is capable of displaying AIS information, it is not required to do so. Based on current rates of navigation system upgrades, it is expected to take at least some years before the substantial percentage of the international commercial fleet will have this capability. Changes in mandatory carriage requirements may accelerate this development for SOLAS vessels. Portable Pilot Navigation Systems may facilitate implementation. Economic benefit to the shipping industry could also provide an impetus to early adoption of this technology.

The nominal report rate of virtual AIS AtoN broadcasts is specified in ITU-R-M.1371. However, due to the limitations in data link capacity IALA Recommendation A-126 recommends a more flexible approach to be considered, taking data link capacity and power consumption at transmitting stations into account.

In the longer term, different report rates may be implemented on different communication media, as appropriate.

The IMO e-Navigation concept includes the need to harmonise the presentation of both shipboard and shore side safety related information. Consideration should be given in implementing virtual AtoN to the harmonisation process within e-Navigation for future applications.

## **8.2 Display**

### **8.2.1 General**

The virtual AtoN should clearly indicate by its name or other relevant attribute the related navigational warning, notice to mariners or other form of MSI relating to the provision of the object.

The display or representation of symbols for virtual AtoN onboard should be standardised. The display of symbols ashore should align to the onboard standard as closely as possible, to facilitate a common interpretation of the maritime situation. (See Reference [23].)

### **8.2.2 Limitations**

In the short to medium term virtual AtoN will not be visible on the displays of many ships and, if visible, the symbols may differ from one display to another. (See section 10.2.)

### **8.2.3 Symbols**

IMO SN/Circ. 243 Annex 2 provides guidance on the use of navigation related symbols on all shipborne navigational systems and equipment.



*Figure 1 The symbol for an AIS AtoN*

No distinction is made between real and virtual AtoN. These navigation related symbols are not

chart symbols<sup>2</sup>.

In IEC 62288 (Navigation Displays) and IEC 62388 (Radars) that came into force in 2008, the diamond is specified for AIS AtoN. For virtual AIS AtoN the diamond has a V inside. This symbol will be implemented as an overlay on navigation equipment (ECDIS, radar etc.) compliant with these specifications. Currently the symbols do not indicate the type of AtoN, although display equipment may allow interrogation to obtain such information.

The ECDIS performance standard requires that overlay symbols should be readily distinguishable from chart symbols. Chart symbols for virtual AIS AtoN are under development by the IHO based on the existing chart symbology for AtoN.

It should be noted that colours for the use of virtual AtoN symbols are not clearly stated for ECDIS overlay and radar display in current specifications.

It should also be noted that IMO is developing new symbols for AIS AtoN scheduled to complete in 2014. The new symbols are expected to clearly distinguish virtual AIS AtoN from physical AIS AtoN and show the type of AIS AtoN.

#### 8.2.4 Point and Area Representation

In addition to the use of the AtoN Report Message 21, emerging application specific messages could be used to provide a representation of a point position, line, area, or other form that may be displayed graphically. There is a need to develop appropriate methods of representation, clearly distinguishable from existing charted symbols.

#### 8.2.5 Expiry and cancellation of virtual AtoN objects

Some virtual AtoN objects (like the AIS AtoN Message 21) rely on repeated transmission to remain valid – however current display standards are not clear on this issue, and implementation may therefore vary in the short to medium term. The timeout limit of a repeatedly transmitted virtual AtoN must be defined in future standards, in order to ensure that the same information is available to all users at all times. (The IEC 62388 radar standards defines when AIS class A and B vessel targets are lost – approximately when the nominal repetition rate has been exceeded by a factor of 6. This general rule is recommended to be implemented for the display of virtual AtoN in future display standards.)

Some virtual AtoN objects (like the emerging application specific messages) may themselves contain a definition of their own lifetime – time of issue and time of expiration. These virtual AtoN objects – and virtual AtoN objects relying on repeated transmissions with repetition, but with a long timeout – should be accompanied by a mechanism for cancellation, in case they become obsolete during their defined lifetime or contain errors. Such a cancellation mechanism also constitutes a mitigation measure to ensure that erroneous or malicious transmissions can be cancelled.

When the lifetime of a virtual AtoN object is timed out or cancelled, it should be removed from display systems. Objects relying on repeated transmissions that have exceeded the nominal reporting rate, but have not yet reached the timeout should, when queried for additional information, clearly indicate that the information may not be up to date.

## 9 NOTIFICATION

Having elected to deploy virtual AtoN, administrations should arrange for detailed information related to such aids to be made available to all concerned.

Administrations should use all available means to ensure that mariners have the necessary information concerning the presence and purpose of virtual aids, including the intended duration of deployment. These means may include MSI broadcast via NAVTEX, INMARSAT Enhanced Group

---

<sup>2</sup> Navigation related symbols are approved and adopted by IMO. Chart symbols are approved and adopted by IHO.

Call (EGC) or VHF/HF/MF radio. The administration should send specific notification to their hydrographic offices for inclusion in notices to mariners and should correct and update relevant paper charts, electronic charts and nautical publications.

As with other aids to navigation, mariners have an obligation to report malfunctioning virtual aids to navigation to the competent authority.

## 10 RISKS AND LIMITATIONS

The virtual AtoN are not visible on the displays of many ships and, if visible, the symbols may differ from one display to another. The consequences may be confusion, lack of information for the user and the undermining confidence in ECDIS, the chart and other systems. It is likely to take at least a decade to harmonise the provision of virtual AtoN as a result of the 'grand-fathering' clauses in the carriage requirement program for ECDIS and the likely schedule for the adoption of Integrated Bridge System (IBS) & e-Navigation.

Radar will only display virtual AIS AtoN as an overlay of a diamond with a V inside if they are compliant with IEC 62388. This test specification came into force in 2008. At the current rate of fitting new equipment, 10-15 years appears to be a realistic timescale for the majority of ships to benefit from the provision of display of virtual AtoN.

Navigational displays compliant with IEC 62288, which came into force in 2008 will show virtual AIS AtoN as an overlay of a diamond with a V inside.

ECDIS equipment fitted prior to 2009 will not show virtual AIS AtoN until the equipment is upgraded or replaced, which is unlikely under the current 'grand-fathering' arrangements. There is currently no provision for virtual AIS AtoN in S-57, or a symbol in S-52, but this is capable of implementation. However, even when virtual AIS AtoN are reflected in S-57 and S-52, existing ECDIS will only show an orange '?' upon encountering a virtual AIS AtoN object in the ENC database. The orange '?' can be interrogated for further detail.

The Minimum Keyboard Display (MKD) should display AIS AtoN, including the virtual flag, but it is known that some MKDs do not meet this requirement.

### 10.1 Risk Mitigation

*Table 1 Potential risk mitigation measures*

Risk	Potential Mitigation
Complete dependence of virtual AtoN	Not rely completely on virtual AtoN but to cross check with other data or information
Not all mariners will receive or be able to display virtual AtoN	MSI should be maintained as primary system, Virtual AtoN supplements MSI Encourage integration with navigation displays, where fitted Development of e-Navigation and S Mode
Information overload	Use of lines and areas versus points Only competent authorities may approve issue Area specific display Development of e-Navigation Limited use of virtual AtoN in any area
Lack of user awareness or understanding	Training Clear promulgation of information Develop educational material

Confusion from varying symbology	Standardisation of symbology by IMO, IHO, IALA, IEC.
Equipment may be set up not to show data	Instruction and training S Mode
Confusion from message options for locations, area and lines	IMO / IALA to define message formats
Loss of signal	Published standards for availability, continuity, integrity Verification of transmission by originator Redundancy Integrity warning Correlation with MSI and / or chart
GNSS vulnerability	AIS semaphore mode Satellite monitoring / RAIM DGNSS integrity message Electronic terrestrial backup
Virtual AtoN vulnerability; jamming / spoofing	Verification of transmission by originator Correlation with MSI and / or charts Data link monitoring by authorities Counter-spoofing (cancelation methods)
No confirmation of receipt of message	Repeated or addressed / acknowledged transmissions Verification of transmission by originator Multiple transmission paths (MSI) Development of e-Navigation
Erroneous message transmitted	Procedures for message checking Verification of transmission by originator
Dynamic prediction accuracy i.e. floating object	Estimation of zone of uncertainty Updated verification Remove position from message after time

## 10.2 Limitations

### 10.2.1 GNSS vulnerability

Ships may lose their positioning capability when the GNSS service is lost due to jamming or interference, unless they have an alternative positioning system. Poor installation or failure of on board equipment can similarly interfere with or degrade GNSS reception.

Delivery of a virtual AtoN Service through the AIS VHF Data Link (VDL) would not necessarily be affected immediately by loss of GNSS, since the position part of the message is fixed and transmitted independent of GNSS.

## 10.2.2 Spoofing and Jamming of Virtual AtoN

Depending on the media, a virtual AtoN service can be spoofed and jammed easily. Jamming can be unintentional or intentional while spoofing would typically be intentional.

Some spoofing methods can be detected through careful monitoring of the transmission channel. One possibility is to monitor MMSI numbers within the service coverage area. Duplicated or non-existing MMSI numbers within the coverage area may indicate spoofing.

Increased spoofing detection capability can be achieved through regional co-operation between neighbouring countries, exchanging valid MMSI numbers and co-operating on identifying invalid MMSI numbers, for example handing over MMSI numbers from one authority to another authority when vessels cross the administrative boundaries of these authorities. Such a scheme is implemented on the administrative boundary between the Malacca and Singapore straits.

Authorities who provide virtual AtoN services should maintain a database of all valid MMSI numbers assigned to virtual AtoN. This database should be shared with such stakeholders as neighbouring countries.

Both spoofing and jamming can compromise and/or shut down a virtual AtoN service. Jamming will typically block the service in a certain geographic region. Spoofing is more sinister since the targeted receiver cannot detect the deception (i.e. the signal appears to be genuine), which could mislead the navigator.

## 10.2.3 AIS VDL capacity and FATDMA planning

Virtual AtoN services transmitted on an AIS VDL typically use the FATDMA protocol.

If the population of virtual AtoN in a given area is too high, this may overload the VDL FATDMA slot capacity. This should be overcome through careful FATDMA planning (IALA Recommendation A-124 refers).

## 10.2.4 Display Limitations

Although there are clear benefits that can be gained by providing safety information through virtual AtoN, it must be borne in mind that very few SOLAS class ships, or other craft, may have the ability to display the virtual AtoN. Some craft may never have the ability to display virtual AtoN.

MKD – All SOLAS class vessels are required to be fitted with a Class A AIS station and many non-SOLAS vessels voluntarily carry Class A AIS or Class B AIS stations. However, currently, few vessels integrate the AIS data into a navigation display such as ECDIS or Radar. The display of virtual AtoN on an AIS MKD is limited to alpha-numeric text and, on some units, a graphic display, although there is no standard for such display.

Radar – Only radars that meet the revised performance standard, which came into force in 2008, have a requirement to be capable of displaying a virtual AIS AtoN. However there is currently no requirement for the AIS to be integrated or displayed on Radar.

ECDIS – ECDIS mandatory carriage requirement for certain classes of SOLAS vessels is being implemented in stages up to 2018, however the current ECDIS performance standard MSC 232(82) does not require AIS or other virtual AtoN to be able to be displayed, nor to be integrated.

Administrations should take into account the limited display capabilities for AIS, or other forms of transmission, for all classes of seaborne craft when assessing the value and risks associated with transmitting virtual AtoN.

# 11 LEVEL OF SERVICE

## 11.1 Availability

The basic principles for categorising AtoN in accordance with their importance is described in Recommendation O-130 (IALA Category 1, 2, or 3). Virtual AtoN Services should be categorised

in the same manner.

If a transmitting site is transmitting signals for multiple virtual AtoN, the most critical one would determine the availability requirements for the service. It should be noted that virtual AtoN transmitting sites must deliver a specified minimum signal strength at the user antenna within a specified service area.

IALA Recommendation A-126 defines the required availability for virtual AIS AtoN and sets the service area criteria in terms of required signal strength.

Similar signal strength criteria should be defined for transmissions transmitted via means other than AIS.

Availability is determined by the ability to deliver the specified reporting rate, signal strength and valid information content. Virtual AtoN criteria should be specified for each of these elements in order to clearly define when the service is no longer available (failure state).

### **11.2 Integrity alerting**

Authorised service providers should have the ability to provide users with warnings within a specified time when a virtual AtoN service is not available.

The warning should be given within a time frame compatible with the criticality of the AtoN (IALA Categories 1, 2 and 3).

Warnings may be issued as MSI and, in the case of AIS, using the flags of message 21, using message 14 or by any other appropriate means.

There is a requirement for integrity monitoring. Such monitoring schemes should be independent of the system providing the basic service. Integrity monitoring can take place both onboard a vessel and ashore.

Shipborne monitoring is limited to validity checking of the received datagram and the reporting rate of the virtual AtoN.

### **11.3 Continuity**

Continuity is the probability that, assuming a fault-free system at the receiving end, the virtual AtoN will be received and displayed on the navigational display over the time interval applicable for a particular operation.

The continuity of a virtual AtoN service should be determined as described in Recommendation R-121. The time interval should be chosen as 3 hours, or a suitable time frame as determined by the authority providing the service. The probability should be according to the category (IALA categories 1, 2 and 3) of each virtual AtoN. If a transmitting site is transmitting signals for multiple virtual AtoN, the most critical one would determine the continuity requirements for the service.

## **12 DEVELOPMENT CONSIDERATIONS**

For the full benefits of virtual AtoN to be realised, a number of issues must be addressed in consultation with other bodies, including:

- appropriate instruction and training of all mariners and providers as to the provision of virtual AtoN, symbology, display, and limitations;
- harmonisation of integration and ship navigation system specification to enable the display of virtual AtoN for SOLAS ships and other users;
- a strategy for implementation of virtual AtoN using non-AIS based systems;
- the harmonisation of the use of MSI by virtual AtoN within the context of the IMO's e-Navigation concept;
- harmonised presentation of virtual AtoN.

## 13 REFERENCES

- [1] IMO Res. A.917(22) 2001 Guidelines for the Onboard Operational Use of Shipborne AIS
- [2] IMO Res. A.956(23) 2003 Amendments to the Guidelines for the Onboard Operational Use of Shipborne AIS
- [3] MSC 232(82) Performance Standards for ECDIS
- [4] MSC.192(79) Performance standards for radar equipment
- [5] MSC.191(79) Performance Standards for the Presentation of Navigation-Related Information on Shipborne Navigational displays
- [6] MSC 86/23/7 New symbols for AIS-AtoN - Submitted by Japan
- [7] IMO SN/Circ 243 – Amendments to Guidelines for the Presentation of Navigation-Related Symbols, Terms and Abbreviations
- [8] IMO SN/Circ 266 Maintenance of ECDIS Software
- [9] IMO SN/Circ 289 Guidance of the Use of AIS Application Specific Messages
- [10] IMO SN/Circ 290 Guidance for the presentation and display of AIS Application Specific Messages Information
- [11] ITU-R M.1371 Technical Characteristics for Automatic identification System using Time Division Multiple Access in the VHF Maritime Mobile Band
- [12] IHO S-4 Chart Specifications of the IHO and Regulations for International (INT) Charts
- [13] IHO S-52 Specifications for Chart Content and Display Aspects of ECDIS
- [14] IHO S-57 Transfer Standard for Digital Hydrographic Data
- [15] IHO S-57 Appendix B.1 ENC Product Specification
- [16] IHO S-100 Universal Hydrographic Data Model
- [17] IHO S-101 ENC Product Specification (ENC Product Specification based on S-100 (not to be adopted before 2012 at the earliest))
- [18] IALA Recommendation R-121 For the performance and monitoring of a DGNSS Service in the band 283.5 – 325 kHz
- [19] IALA Recommendation A-124 on the AIS Service
- [20] IALA Recommendation A-126, on the Use of the Automatic Identification System (AIS) in Marine Aids to Navigation Services, Edition 1.5, Jun. 2011
- [21] IALA Recommendation O-130 on Categorisation and Availability Objectives for Short Range Aids to Navigation
- [22] IALA Guideline 1062 on the establishment of AIS as an Aid to Navigation
- [23] IALA Recommendation V-125 on the Use and Presentation of Symbology at a VTS Centre (including AIS)
- [24] IEC 61174 ECDIS – Operational and Performance Requirements, Methods of Testing and Required Test Results
- [25] IEC 61193-2 Class A shipborne equipment of the universal automatic identification system (AIS) - Operational and performance requirements, methods of test and required test results AIS Class A
- [26] IEC 62288 Presentation of navigation-related information on shipborne navigational displays
- [27] IEC 62320-2 AIS AtoN stations - Minimum operational and performance requirements - methods of test and required test results

[28] IEC 62388 Maritime navigation and radio-communication equipment and systems –  
Shipborne radar - Performance requirements, methods of testing and required test results

## 14 ACRONYMS / INITIALISMS

AIS	Automatic Identification System
AtoN	Aids to Navigation
DGPS	Differential Global Positioning System
ECDIS	Electronic Chart Display and Information System
ECS	Electronic Chart System
EGC	Enhanced Group Calling
FATDMA	Fixed Access Time Division Multiple Access
GNSS	Global Navigation Satellite System
GPRS	General Packet Radio Service
GPS	Global Positioning System
HF	High Frequency
IALA	International Association of Marine Aids to Navigation and Lighthouse Authorities
IBS	Integrated Bridge System
IEC	International Electro-technical Commission
IHO	International Hydrographic Organization
IMO	International Maritime Organization
INMARSAT	International Maritime Satellite Organization
ITU	International Telecommunication Union
ITU-R	ITU Radiocommunications Sector
ITU-R-M	ITU-R M series Recommendations and ITU-R M series Reports
LORAN	LONG RANGE Navigation
MF	Medium Frequency
MIO	Marine Information Overlay
MKD	Minimum Keyboard and Display
MMSI	Maritime Mobile Service Identity
MSC	Maritime Safety Committee (IMO)
MSI	Maritime Safety Information
NAV	Sub-Committee on Safety of Navigation (IMO)
NAVTEX	Navigational Telex
RAIM	Receiver Autonomous Integrity Monitoring
RCC	Rescue Co-ordination Centre
SAR	Search and Rescue
SN/Circ.	Safety of Navigation Circular (IMO)
SOLAS	United Nations Convention on Safety of Life at Sea
t.b.d.	to be decided

Virtual AtoN	Virtual Aid to Navigation
VDL	VHF Data Link
VHF	Very High Frequency
VTS	Vessel Traffic Services
VTSO	Vessel Traffic Services Operator
WiMAX	Worldwide Interoperability for Microwave Access

## ANNEX A APPLICATION OF VIRTUAL AIDS TO NAVIGATION

Note:

**The use of virtual AtoN is only suitable for vessels that have appropriate display equipment.**

<i>Application Mode</i>	Function	Description	Type of Virtual AtoN AIS	Consideration
<i>Permanent Marking of Obstacles</i>	Marking of Shoals and Reefs	Virtual AtoN can be effectively utilized where it is difficult to place or to maintain a physical AtoN due to sea state, winds or other environmental conditions. A clear marking of the shoals and/or reefs will improve safety of navigation	Isolated Danger Marks & Cardinal Marks	<ul style="list-style-type: none"> <li>Integrity monitoring</li> <li>ECDIS and radar reliability</li> </ul>
<i>Permanent Marking (navigation support)</i>	Marking of Fairway Limits	Virtual AtoN can be effectively utilized where a physical AtoN placement is difficult due to the water depth, seabed, etc.  A clear marking of the fairway limits serve for ordinary flow of marine traffic and improved safety of navigation.	Lateral Marks	<ul style="list-style-type: none"> <li>Too much information for mariners</li> </ul>
	Marking of Fairways	Virtual AtoN can be effectively utilized where a physical AtoN placement is difficult due to the water depth, seabed, etc.  A clear marking of fairway will improve safety of navigation.	Lateral Marks, & Safe Water Marks	<ul style="list-style-type: none"> <li>Too much information for mariners</li> </ul>
		Virtual AtoN can be effectively utilized in approaches to a harbour entrance where a ship changes its course and where it is difficult to install a physical AtoN.  A clear marking of the point on approach will serve for an orderly flow of ships at an entrance and improve	Safe Water Marks	<ul style="list-style-type: none"> <li>Too much information for mariners</li> </ul>

		safety and efficiency of shipping.		
	Marking of Fairways & Marking of the Limits of Safe Waters	Virtual AtoN can be effectively utilized where navigation becomes difficult due to a thick fog, heavy rain, etc. (This application can also be adapted as a temporary marking during limited visibility.)  Marking of a recommendable fairway during times of limited visibility will serve to improve safety of navigation and efficiency of shipping.	Lateral Marks & Safe Water Marks	<ul style="list-style-type: none"> <li>• Should be temporary</li> </ul>
<i>Permanent Marking</i>	Special area (e.g. anchorage area, area to be avoided)	Virtual AtoN can be effectively utilized where pre-caution or special caution required.  A clear marking of special area will improve safety of navigation.	Special Marks	<ul style="list-style-type: none"> <li>• Too much information for mariners</li> </ul>
<i>Temporary Marking</i>	Marking of a Navigational Restricted Areas	Virtual AtoN can be effectively utilized when navigation restriction is required due to e.g., marine accidents or when marking of wreck or offshore operations.  A temporary navigation restriction can prevent subsequent incidents from developing.	Cardinal Marks, Emergency Wreck Marks, Isolated Danger Mark & Special Marks	<ul style="list-style-type: none"> <li>• Need to be monitored / updated</li> <li>• Timely deployment required</li> </ul>
	Designation of Temporarily Recommendable Fairways	Virtual AtoN can be effectively utilized for indication of fairways when a scale disaster hits the area.  A clear marking of temporarily recommendable fairways will be expected to serve for the relief ships dispatched to the site and to support safe	Lateral Marks & Safe Water Marks	<ul style="list-style-type: none"> <li>• Need to be monitored / up dated</li> <li>• Timely deployment required</li> </ul>

		and effective relief activities.		
	Marking of Aids to Navigation that are malfunctioning or off position	<p>Virtual AtoN AIS can be effectively utilized when a physical AtoN has lost ability to perform regular functions due to a natural disaster.</p> <p>When a physical AtoN has lost its ability to perform regular functions due to natural disasters, recovery actions are required at the earliest opportunity. Virtual AtoN can respond to the circumstance, even if the actions by personnel cannot be achieved due to meteorological and/or hydrographical conditions, and keep the influence of the disaster on ships navigating at a minimum level.</p>	Cardinal Marks, Lateral Marks, Isolated Danger Marks, Safe Water Marks & Other Position Marks	<ul style="list-style-type: none"> <li>• Timely deployment required</li> </ul>
<i>Temporary Marking</i>	Pilot boarding station	Virtual AtoN will be useful to mark a pilot station where position depends on sea condition.	Special Marks	<ul style="list-style-type: none"> <li>• Timely deployment required</li> </ul>